



Grossing workstations



Safety



Efficiency



Quality



R+D+i

📍 Calle Lanzarote 11, Nave 8
28700 San Sebastián de los Reyes, Madrid.

☎ Tel.+34 91 659 15 06 | Fax. +34 91 653 09 57

@ info@fvhoods.com 🌐 www.fvhoods.com

hoods  **Flores Valles**
division



hoods  **Flores Valles**
division

What makes us different?



Dimensions (mm)	1 user	2 users	
A	1.200	1.700	2.000
B		830	
C		2.100	
Worktop height (mm)			
D		900	
Weight (Kg)	275	345	405
Drain (mm)		DN40	
Water Inlet connexion		1/2" female	
Exhaust collar (mm)		250	
Electrical feed		230V - 50/60 Hz - Ph+N+PE	
Power consumption (W)		280	
Face velocity (m/s)		0,4 - 0,5	
Flow rate range (m³/h)	280 - 1250	420 - 1800	
Formaldehyde filter (Bi-On +)	1	2	
Activated charcoal filter (class F5)	1	2	
Internal lighting		1600 Lux IP65	
Germicidal UV Light (253,7 nm)	25 W	30 W	2x25W



Safety

- Specific filters for formaldehyde (Active carbon and potassium + particle filter F5).
- Safety sash guaranteeing the maximum protection and containment.
- Touch control panel with acoustic and visual alarm:
 - Low exhaust flow.
 - Filter replacement.
 - Over opening of the sash.
 - Empty/Full drums level.
- Presence sensor:
 - Lighting auto power OFF.
 - Automatic closing down of the sash.
 - UV light power OFF.
- UPS System: Against power cuts (6h autonomy).
- VAV System (Variable Air Volume) depending on the sash opening.



Efficiency

- Minimal sound level (< 50 db).
- LED lighting (> 1000 lux).
- Energy saving: VAV system and presence detector.
- Easy maintenance: Guided filter replacement and easy access to the electronic connection box.



Quality and ergonomics

- Maximum visibility: front and side protection made in glass.
- Rounded surfaces for an easy cleaning.
- Securized glass shelves easily demountable.
- Magnetic accessible support on the side for cutting tools.
- Shower tap and automatic activation tap.
- Wheel-support system for mobility and blocking.
- Magnifying glasses with LED light for each working area.



R+D+i

- Formalin module dispenser (airtight screw caps and level sensor adapted to the formalin drums).
- Recirculating system or piping system (extraction plenum).
- Customized worktop.
- Automatic sink washing.
- Monitor bracket and accesories.
- Adaptable to new requirements.
- Continuous development.
- Manufactured in AISI 304 or 316.

